






RoHS



Specification:

- Current Rating: 2A AC/DC
- Voltage Rating: 125V AC/DC
- Insulation Resistance: 1000MΩ(Min)
- Contact resistance: 20mΩ(Max).
- Withstanding Voltage: 800VAC(Min)
- Operation Temperature: -25°C to +85°C


Material:

- Wire Range: 24AWG~28AWG
- Insulation O.D: 1.4mm Max
- Material: Phosphor Bronze, T=0.15mm
- Finish: Tin Plated

Ordering Information

SCT2002T P S 106

Material:
P=Phosphor Bronze S=Tin Plated

					OPERATION	DRAW	Peng	2021.07.10	SCALE	-	 SCONDAR ELECTRONIC LIMITED	
					X.X ±0.35	DESIGN			UNIT	mm		
					X.XX ±0.25		CHECK	Lisa	2021.07.10	SIZE		A4
A1	2021.07.10	Changed from SCT2002TP to SCT2002TPS106			X.XXX ±0.15	APPROVE	Allen	2021.07.10	SHEET	1/1	PART NO.	SCT2002TPS106
AO	2009.03.03	NEW			Angle ± 3'				PROJ.	⊕	TITLE:	MX51004 2.00mm Terminal
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	TOL						

