

RoHS

Specification:

- Current Rating: 3A AC/DC
- Voltage Rating: 250V AC/DC
- Insulation Resistance: 1000MΩ Min
- Withstanding Voltage: 800VAC(1Min)
- Contact resistance: 20mΩ(Max).
- Operation Temperature: -25°C to +85°C

Material:

- Insulator (Housing): Nylon 66 (UL94V-0)
- Color: Black

受控

Ordering Information





SCT2011H - 2xx B BK 107

No.of Pins  
See Table

Insulation  
B=PA66

Color  
BK=Black

2*11	20.00	24.00			
2*10	18.00	22.00	2*20	38.00	42.00
2*9	16.00	20.00	2*19	36.00	40.00
2*8	14.00	18.00	2*18	34.00	38.00
2*7	12.00	16.00	2*17	32.00	36.00
2*6	10.00	14.00	2*16	30.00	34.00
2*5	8.00	12.00	2*15	28.00	32.00
2*4	6.00	10.00	2*14	26.00	30.00
2*3	4.00	8.00	2*13	24.00	28.00
2*2	2.00	6.00	2*12	22.00	26.00
Poles	A	B	Poles	A	B
	Dimensions			Dimensions	



东莞市融凯达电子科技有限公司  
工程专用章

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	Peng	2021.07.12	SCALE	-	 SCONDAR ELECTRONIC LIMITED	
A1	2021.07.12	Changed from SCT2011H-2xxP to SCT2011H-2xxBBK107			X.X	±0.35			UNIT	mm		
AO	2009.10.15	NEW			X.XX	±0.25			SIZE	A4		
					X.XXX	±0.15			SHEET	1/1		
					Angle	± 3'			PROJ.	☉	PART NO.	SCT2011H-2xxBBK107
					DIM	TOL					TITLE:	DF11 2.00mm Pitch Housing Connector