






RoHS





Specification:
 -Current Rating: 1.5A AC/DC
 -Voltage Rating: 100V AC/DC
 -Insulation Resistance: 100MΩ Min
 -Withstanding Voltage: 500VAC(1Min)
 -Contact resistance: 20mΩ(Max).
 -Operation Temperature: -25°C to +85°C
 Material:
 -Insulator (Housing): PA9T (UL94V-0)
 -Color: Beige
 -Contacts: Brass/Tin Plated



Ordering Information


SCT1503WRS -2xx E 1 BE 113

No. of Pins See Table
 Insulation E=PA9T V0
 Package 1=Tape&Reel
 Color BE=Beige




Recommended P.C.B. Layout
 Total tolerance:±0.05mm


Dimensions			Part NO	PIN
A	B	C		
4.50	10.30	8.93	SCT1503WRS-204E1BE113	2x4
6.00	11.80	10.43	SCT1503WRS-205E1BE113	2x5
7.50	13.30	11.93	SCT1503WRS-206E1BE113	2x6
9.00	14.80	13.43	SCT1503WRS-207E1BE113	2x7
10.50	16.30	14.93	SCT1503WRS-208E1BE113	2x8
12.00	17.80	16.43	SCT1503WRS-209E1BE113	2x9
13.50	19.30	17.93	SCT1503WRS-210E1BE113	2x10
15.00	20.80	19.43	SCT1503WRS-211E1BE113	2x11
16.50	22.30	20.93	SCT1503WRS-212E1BE113	2x12
18.00	23.80	22.43	SCT1503WRS-213E1BE113	2x13
19.50	25.30	23.93	SCT1503WRS-214E1BE113	2x14
21.00	26.80	25.43	SCT1503WRS-215E1BE113	2x15
22.50	28.30	26.93	SCT1503WRS-216E1BE113	2x16
24.00	29.80	28.43	SCT1503WRS-217E1BE113	2x17
25.50	31.30	29.93	SCT1503WRS-218E1BE113	2x18
27.00	32.80	31.43	SCT1503WRS-219E1BE113	2x19
28.50	34.30	32.93	SCT1503WRS-220E1BE113	2x20




2X4-2X5P



2X6-2X9P



2X9-2X15P



2X16-2X20P

SCONDAR ELECTRONIC LIMITED
 ENGINEER L10 APPROVED

AO	NEW				OPERATION	DRAW	zhong	2019.10.12	SCALE	—	 SCONDAR ELECTRONIC LIMITED
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	X.X ±0.30	DESIGN			UNIT	mm	
					X.XX ±0.20	CHECK	Lisa	2019.10.12	SIZE	A4	
					X.XXX ±0.10	APPROVE			SHEET	1/1	
					Angle ±3°				Part No.	SCT1503WRS-2xxE1BE113	
					DIM TOL				PROJ.	TITLE:	MX1.5mm 2XxxP PA9T V0 Beige SMT WR Socket