



**SPECIFICATIONS**

Voltage Rating: 250V AC/DC  
 Current Rating: 2A AC/DC  
 Withstanding Voltage: 500V AC/minute  
 Insulation Resistance: 1000MΩ min.  
 Temperature Range: -25° C - +85° C  
 Contact Resistance: 20mΩ max

**HOUSING**

Part No: SCT2544H-XXP  
 Poles: 2-10  
 Material: PA66, UL94V-2

PART NO.	Dimensions	
	A	B
SCT2544H-02P	2.54	5.08
SCT2544H-03P	5.08	7.62
SCT2544H-04P	7.62	10.16
SCT2544H-05P	10.16	12.70
SCT2544H-06P	12.70	15.24
SCT2544H-07P	15.24	17.78
SCT2544H-08P	17.78	20.32
SCT2544H-09P	20.32	22.86
SCT2544H-10P	22.86	25.40
SCT2544H-11P	25.40	27.94
SCT2544H-12P	27.94	30.48
SCT2544H-13P	30.48	33.02
SCT2544H-14P	33.02	35.56
SCT2544H-15P	35.56	38.10
SCT2544H-16P	38.10	40.64
SCT2544H-17P	40.64	43.18
SCT2544H-18P	43.18	45.72
SCT2544H-19P	45.72	48.26
SCT2544H-20P	48.26	50.80

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	OPERATION	DRAW	YANG	2016.05.19	SCALE	SCONDAR 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
0	05/12/27	NEW			~ 10 ±0.15	DESIGN			UNIT	mm	PART NO. SCT2544H-XXP
					20 ~ 30 ±0.30	CHECK	MICKY	2016.05.19	SIZE	A4	TITLE: MX2.54 CD-ROM HOUSING
					30 ~ ±0.50	APPROVE	ALLEN	2016.05.19	SHEET	1/1	DRAWING NO. SCT2544H
					Angle ± 2'				PROJ.		
					DIM TOL						