

RoHS

Specification:

- Current Rating: 3A AC/DC
- Voitage Rating: 250V AC/DC
- Insulation Resistance: 1000MΩ Min
- Withstanding Voltage: 1500VAC(1Min)
- Contact resistance: 10mΩ(Max).
- Operation Temperature: -40℃ to +85℃

Material:

- Insulator (Housing): PA66 (UL94V-2)
- Color: Red

Ordering Information

SCT2548HIR - xx C RD 140

No.of Pins
See Table

Insulation
C=PA66 V0
Color
RD=Red

C	Color	Wire size
R	Red	#22
W	White	#24
N	Natural	#24
B	Black	#24
b	Blue	#26
G	Green	#26

10	22.86	25.40			
9	20.32	22.86			
8	17.78	20.32	17	40.64	43.18
7	15.24	17.78	16	38.10	40.64
6	12.70	15.24	15	33.56	38.10
5	10.16	12.70	14	33.02	33.56
4	7.62	10.16	13	30.48	33.02
3	5.08	7.62	12	27.94	30.48
2	2.54	5.08	11	25.40	27.94
Poles	A	B	Poles	A	B
	Dimensions			Dimensions	

东莞市晟凯达电子科技有限公司
工程专用章

受控

					OPERATION	DRAW	Peng	2021.07.07	SCALE	—	 SCONDAR ELECTRONIC LIMITED			
					X.X	±0.35			UNIT	mm				
					X.XX	±0.25			SIZE	A4				
A1	2021.07.07	Changed from SCT2548HIR-xxP to SCT2548HIR-xxCRD140			X.XXX	±0.15			SHEET	1/1	PART NO.	SCT2548HIR-xxCRD140		
AO	2019.10.15	NEW			Angle	± 3°								
REV	DATE	MODIFICATION DESCRIPTION			DIM	TOL	APPROVE	Allen	2021.07.07	PROJ.	TITLE:	AMP640440 90C IDC HOUSING		