






RoHS



受控

东莞市晟凯达电子科技有限公司
工程专用章



Technical parameters:

Rated voltage: 1500V
 Insulation material: ppo
 Conductor material: copper tin plating
 Ambient temperature: - 40° C ~+95° C
 Product temperature resistance: - 40° C~+135° C
 Safety level: DCII
 Waterproof grade: IP68
 Contact resistance: <=0.5mΩ
 Connecting systems: multipoint connections
 Self locking system: embedded
 Wiring mode: crimping
 Wiring specification: 2.5mm² 4mm² 6mm²
 Rated current: 17A (1.5mm²) 22A(2.5mm²)
 30A(4mm² ~ 6mm²)
 Flame retardant grade: UL94-V0
 Plastic unmarked tolerance: ±0.5
 Terminal unmarked tolerance: ±0.2

ordering information

SCT PZ - V2 XX 2 02 641

— Type voltage current Entrance and exit Shape Series
 V2=1500V 17=17A 25=25A 2=2PASS
 30=30A

						OPERATION	DRAW	Yang	2020.05.03	SCALE	-	 SCONDAR ELECTRONIC LIMITED	
						X.X ±0.35	DESIGN			UNIT	mm		
						X.XX ±0.25	CHECK	Lisa	2020.05.03	SIZE	A4		
						X.XXX ±0.15	APPROVE			SHEET	1/1		PART NO. SCTPZ-V2XX202641
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE		Angle ± 3'				PROJ.	⊕	TITLE:	PV through voltage: 1500V, current: xA
						DIM TOL							