

PCB LAYOUT

SPECIFICATIONS


- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 300V AC, DC
- 3、Temperatuer Range: -40°C~+105°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 1700V AC/minute
- 7、Material:Wafer LCP,UL94V-0  
PIN Phosphoric bronze Tin-plated  
Solder tad Phosphoric bronze Tin-plated

Ordering Information

400BTB-MWR-02 S F 1 BE 182

F=Female  
M=Male  
Plating  
S=Tin Plated  
Material  
F=LCP  
Package  
1=Tape&Reel  
Color  
BE=Beige

SCONDAR ELECTRONIC LIMITED  
ENGINEER LIU APPROVED

						OPERATION	DRAW	Zhong	2020.11.03	SCALE		 森康达电子有限公司 SCONDAR ELECTRONIC LIMITED	
						~ 10 ±0.15	DESIGN			UNIT	mm		
						20 ~ 30 ±0.30				SIZE	A4	PART NO.	400BTB-MWR-02SF1BE182
0	05/12/27		NEW			30 ~ ±0.50	CHECK	Micky	2020.11.03	SHEET	1/1	TITLE:	BTB4.0mm 02Pin male SMT Right angle Header LCP V0 Beige Tin(Sn) Plating Tape and Reel MPQ=1KPcs
REV	DATE		MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle DIM TOL	APPROVE			PROJ.			