








RoHS



SECTION A-A



RECOMMENDED PCB LAYOUT



APPLICABLE FPC

SPECIFICATION:

- Rated Current: 0.5A
- Rated voltage: 50V AC
- Insulation Resistance: 500MΩ Min
- Withstand voltage: 500VAC (1Min)
- Contact resistance: 30mΩ (Max)
- Working temperature: -25°C to +85°C

Material:

- Housing: LCP (UL94V-0) Beige
- Actuator: LCP (UL94V-0) Black
- Fitting Nail: Phosphor Bronze
- Plating: Surface nickel plating, followed by Tin plating
- Contact: Phosphor Bronze
- Plating: Surface nickel plating, followed by Tin plating

Ordering Information

FPC 05 20 A1 - xxP RS S S 1 101

Pitch 05=0.5mm Height H=2.0mm Model No.of Pins See Table Type SMT WR Foot Position X=Bottom contact S=Top contact Coating G=Gold S=Tin Package 1=Tape&Reel 2=Tube

PIN	Dim A	Dim B	Dim C	PIN	Dim A	Dim B	Dim C
4	1.50	2.56	8.20	25	12.00	13.06	18.70
5	2.00	3.06	8.70	26	12.50	13.56	19.20
6	2.50	3.56	9.20	27	13.00	14.06	19.70
7	3.00	4.06	9.70	28	13.50	14.56	20.20
8	3.50	4.56	10.20	29	14.00	15.06	20.70
9	4.00	5.06	10.70	30	14.50	15.56	21.20
10	4.50	5.56	11.20	32	15.50	16.56	22.20
12	5.50	6.56	12.20	33	16.00	17.06	22.70
13	6.00	7.06	12.70	34	16.50	17.56	23.20
14	6.50	7.56	13.20	35	17.00	18.06	23.70
15	7.00	8.06	13.70	36	17.50	18.56	24.20
16	7.50	8.56	14.20	40	19.50	20.56	26.20
18	8.50	9.56	15.20	45	22.00	23.06	28.70
20	9.50	10.56	16.20	50	24.50	25.56	31.20
22	10.50	11.56	17.20	54	26.50	27.56	33.20
23	11.00	12.06	17.70	55	27.00	28.06	33.70
24	11.50	12.56	18.20	60	29.50	30.56	36.20

SCONDAR ELECTRONIC LTD
ENGINEER LIU APPROVED

AO	2021.06.06	NEW			OPERATION	DRAW	YAO	2021.06.06	SCALE	-	<p>SCONDAR ELECTRONIC LIMITED</p>
					X.X	±0.35			UNIT	mm	
					X.XX	±0.25			SIZE	A4	
					X.XXX	±0.15			SHEET	1/1	
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	Angle	± 3'			PART NO.	FPC0520A1-XXPRSS1101	
					DIM	TOL			PROJ.	TITLE:	FPC 0.5mm H=2.0 'A' Model number Full type SMT RS LCP VO Beige TOP CONTACT xxP Contact Tin plating Reel Package